

VARIABLE SPEED DRIVES

0,2 TO 2,2 KW

* INTEGRATED EMC FILTER *

* 2 YEARS GUARANTEE *

TECHNICAL CHARACTERISTICS:

- CE, UL and cUL approvals
- Thermostatic cooling fan
- Basic & Advanced set-up parameters
- DIN rail mounting
- PNP or NPN operation
- V/F and sensorless vector operating modes
- PC and PDA set-up / test software
- PID control, with sleep operation
- Remote keypad option
- 8 preset frequencies
- DC braking
- Multi-function & RS232 and 485 option cards

SPECIFICATIONS:

- Overload (A) = 150% for 60s
- Maximum operating temperature IP20 = 50°C
- Maximum output frequency = 200Hz
- Carrier frequency = 4~16kHz
(Derating applies above 10kHz)
- Safety Class = UL508C



Ref. ABE	Description
VARI.EDX040-21E	0,4 KW 220V 1-phase
VARI.EDX075-21E	0,75 KW 220V 1-phase
VARI.EDX150-21E	1,5 KW 220V 1-phase
VARI.EDX220-21E	2,2 KW 220V 1-phase
VARI.EDX150-43E	1,5 KW 400V 3-phase
VARI.EDX220-43E	2,2 KW 400V 3-phase